CEJN Blow Guns – Series 208

208 Blow Gun Features

- Easy connection
- Ergonomically designed for comfortable handling
- Suspension possible by both the built-in hook and the handle
- The normal grip is adjusted to fit the hand during normal usage
- Extremely durable acetal plastic that also isolates against cold media
- Infinitely variable airflow with high volume flow for efficient cleaning

SPECIFICATIONS	
Max. working pressure	Standard blow guns: 16 bar (232 psi) 8 bar (116 psi) blow gun with regulator
Temperature range	-20°C to +60°C (-4°F to +140°F)
MATERIALS	
Body	POM
Nozzle	Brass

APPLICABLE SAFETY STANDARDS

OK — The products with the 'OK' symbol are compliant with the OSHA directive STD1-13.1 (1910-242(b)). When dead ending occurs, static pressure at the main orifice shall not exceed 30 psi (2 bar).

The products with the 'EAR' symbol are compliant with the International Standard ISO 4414 – Pneumatic Fluid Power & OSHA 1910.95 – Occupational Noise Exposure. These products have a sound level below 85 dBA & meet the EU Machine Directive §1.5.8. concerning noise reduction demands.

BLOW GUNS – SERIES 208

BLOW GUN WITHOUT NOZZLE
1/4" BSPT 620

PART NUMBER	NOZZLE LENGTH	FLOW CAPACITY	NOISE LEVEL
C112080000	N/A	820 l/min	105 dB

OK

BLOW GUN WITH REGULATOR AND REMOVABLE NOZZLE
1/4" BSPT 620

PART NUMBER	NOZZLE LENGTH	FLOW CAPACITY	NOISE LEVEL
C112080300	90 mm	250 l/min	93 dB

BLOW GUN WITH NON-REMOVABLE NOZZLE
1/4" BSPT 620

PART NUMBER	NOZZLE LENGTH	FLOW CAPACITY	NOISE LEVEL
C112080100	90 mm	500 l/min	96 dB

WITH REMOVABLE NOZZLE

C112080200	90 mm	500 l/min	94 dB

OK

BLOW GUN WITH NON-REMOVABLE STAR-TIP
1/4" BSPT 620

PART NUMBER	NOZZLE LENGTH	FLOW CAPACITY	NOISE LEVEL
C112083100	90 mm	190 l/min	79 dB

WITH REMOVABLE STAR-TIP

C112083200	90 mm	190 l/min	79 dB

BLOW GUN DISPLAY CASE

20 PIECE BLOW GUN DISPLAY CASE
620

PART NUMBER	DESCRIPTION
C112089984	20 x C112080100

SAFETY

Did you know?

Products with safety benefits are indicated by a chevron at the bottom of their table